

Discovery 60 PCB Image Processor



The Discovery 60 PCB uses an FPGA in addition to dual-core processor technology to provide a powerful FPGA+DSP platform capable of executing a complete suite of real-time video image-processing functions simultaneously. It also includes an ARM-9 general-purpose microprocessor running embedded Linux for robust user-interface and control implementations.

The Discovery 60 PCB runs applications firmware from Pixion Imaging's Discovery Algorithm Suite to provide an exceptionally powerful a turn-key video image-processing system for military, homeland security, surveillance, scientific, and other high-end imaging applications.


Specifications

Video inputs	
Video In	75 ohm, composite (CVBS, RS-170), 1 V p-p, NTSC or PAL format
Video outputs	
Video Out	Composite (CVBS, RS-170), 1 V p-p into 75 ohm load, video format same as "Video In" signal
Video loop-through	Composite (CVBS, RS-170), 1 V p-p into 75 ohm load, buffered "Video In" signal
Video bypass feature	
Video-signal-processing bypass (solid-state switching), software-controlled or hardware external control (logic-level); default mode on power-down or watchdog failure is bypass	Buffered output
Alternate power input	
3.3 to 5.5 VDC, 40 mA maximum	Alternative power input to maintain bypass and loop-through amplifiers if main power source fails
Control ports	
Serial port	RS-232 or +3.3 V UART, Switch-selectable
GPIOs	
Logic-level I/O (each line programmable as input or output)	6 lines, 1.8 V logic levels, unbuffered (external buffers and ESD protection may be required)
Power requirements	
Supply voltage	5.0 VDC $\pm 10\%$
Load regulation	$\pm 5\%$, maximum ripple 50 mV p-p, transient response 2 ms for 50% load change
Line regulation	$\pm 5\%$

Supply current	650 mA typical (at 5.0 VDC)
Environmental	
Ambient temperature range, operating [1]	0 to 70 °C standard
Ambient temperature range, storage	-60 to 85 °C
Humidity	3% – 90%, non-condensing
Dimensions	
H x W x D (with MCX extension, 90-deg MCX connectors)	50.0 x 86 x 14.0 mm
Weight (with MCX extension, 90-deg MCX connectors)	67 g

Software	
Region of interest - Selects region of video to be processed	
Brightness control - Dynamic range control for adjusting the balance between dark and light areas	
Power contrast - Sharpens features in low contrast areas and increases the difference between the light and dark portions for each feature	
Dehazing - Color recovery and haze (rain, fog, smoke, dust, murky water) removal	
Noise reduction - Removes noise by frame averaging	
Motion adaptive noise reduction - Removes noise in stationary features and leaves moving features unprocessed so they don't disappear	
Gamma correction - Controls brightness, similar to the brightness function on a TV or computer monitor	

Mechanical drawing





For more information

Please visit our website at www.pixionimaging.com or contact us directly at:

Pixion Imaging, a Micro USA company
12875 Brookprinter Pl, #200
Poway, CA 92064
+1-619-227-2739 tel

IMPORTANT NOTICE

Pixion Imaging reserves the right to make corrections, modifications, enhancements, improvements, and other changes to its products and services at any time and to discontinue any product or service without notice. Customers should obtain the latest relevant information before placing orders and should verify that such information is current and complete. All products are sold subject to Pixion Imaging's terms and conditions of sale supplied at the time of order acknowledgment.

Pixion Imaging warrants performance of its hardware products to the specifications applicable at the time of sale in accordance with Pixion Imaging's standard warranty. Testing and other quality control techniques are used to the extent Pixion Imaging deems necessary to support this warranty. Except where mandated by government requirements, testing of all parameters of each product is not necessarily performed.

Pixion Imaging assumes no liability for applications assistance or customer product design. Customers are responsible for their products and applications using Pixion Imaging components. To minimize the risks associated with customer products and applications, customers should provide adequate design and operating safeguards.

Pixion Imaging does not warrant or represent that any license, either express or implied, is granted under any Pixion Imaging patent right, copyright, mask work right, or other Pixion Imaging intellectual property right relating to any combination, machine, or process in which Pixion Imaging products or services are used. Information published by Pixion Imaging regarding third-party products or services does not constitute a license from Pixion Imaging to use such products or services or a warranty or endorsement thereof. Use of such information may require a license from a third party under the patents or other intellectual property of the third party, or a license from Pixion Imaging under the patents or other intellectual property of Pixion Imaging.

Reproduction of Pixion Imaging information in Pixion Imaging manuals or data sheets is permissible only if reproduction is without alteration and is accompanied by all associated warranties, conditions, limitations, and notices. Reproduction of this information with alteration is an unfair and deceptive business practice. Pixion Imaging is not responsible or liable for such altered documentation. Information of third parties may be subject to additional restrictions. Resale of Pixion Imaging products with statements different from or beyond the parameters stated by Pixion Imaging for that product voids all express and any implied warranties for the associated Pixion Imaging product and is an unfair and deceptive business practice. Pixion Imaging is not responsible or liable for any such statements.

Pixion Imaging products are not authorized for use in safety-critical applications (such as life support) where a failure of the Pixion Imaging product would reasonably be expected to cause severe personal injury or death, unless officers of the parties have executed an agreement specifically governing such use. Buyers represent that they have all necessary expertise in the safety and regulatory ramifications of their applications, and acknowledge and agree that they are solely responsible for all legal, regulatory and safety-related requirements concerning their products and any use of Pixion Imaging products in such safety-critical applications, notwithstanding any applications-related information or support that may be provided by Pixion Imaging. Further, Buyers must fully indemnify Pixion Imaging and its representatives against any damages arising out of the use of Pixion Imaging products in such safety-critical applications.

Trademarks

"Pixion", "Pixion Imaging", "Discovery 60", "Better Vision, Everywhere", and the Pixion Imaging logotype are trademarks of Pixion Imaging.

Copyright notice

This document and its contents are copyrighted © 2012 Pixion Imaging. All rights, including electronic reproduction transmission, and storage are reserved.